EXAMPLE OF COLORS AND HANDLE TYPES

GU DIRIGENT

Colours of the handles:

standard + pull: titanium, old gold F4, stainless steel, anthracite RAL 7016, black RAL 9005, crem RAL 9001, brown UC5, white RAL 9016, silver EV1

two-sided and PZ: as standard except crem RAL 9001

SELECTED VENEERS



>> profile core colour: only white

The actual colours may differ from the printed ones. Window profiles can be covered with foil, lacquered or colored in mass. For full colour palette ask our sales representatives or visit amex-baczek.com.



"AMEX-BACZEK" SP. Z O. O. SP. K.

Falknowo 13, 14-240 Susz tel. +48 89 648 69 03 contact@amex-baczek.com amex-baczek.com NIP 744 14 85 088 REGON 510815144



f in 🖸 🗗 🛩 amex-baczek.com



V-MOTION 82



The information included in this leaflet is for information purposes only. Before purchasing a product, the specification should be verified with the manufacturer or sales representative.







MAXIMUM FRAME DIMENSIONS*

Scheme A


white: width 6000 mm; height 2700 mm color: width 5000 mm; height 2500 mm

Scheme C

white: width 6500 mm; height 2700 mm color: width 6500 mm; height 2500 mm


> *The dimensions are for information only and may have additional restrictions. For details, ask the Amex-Baczek Sales Department or our Trade Partners.

SCHEME A



Two-part door with lift-and-slide door-leaf and glazed fixed part

SCHEME C




Four-part door with 2 lift-and-slide leaves opened to the outside


and 2 glazed fixed parts

FIXED GLAZING TT TO TO TO TO R R M the frame can turn thanks to (no need to screw into steel) two separate frame chambers for steel 60 x 40 mm PVC guide profile with the aluminum overlay to hide the screw a multi-chamber profile covering the frame prevents deformation optimum transfer of the glass weight to the threshold thanks to specially designed steel reinforcement for sliding and fixed sashes symmetrical connecting profile with extruded seals to attach the fixed sash in the frame reliable sealing between the threshold and the frame and the sash thanks to two glazing up to 54 mm optimised seals in the sash, connected to each other at the corner a continuous adapter profile with the integrate new PVC threshold (105.422) seal and fixing of the Two types of bands: - zero threshold (0°) with two separate steel chamb 50 x 20 mm and 60 x 40 mm aluminum overlav Two types of aluminum rboard 3° are ava in VEKA threshold: <u>i</u> 55 The


V-MOTION 82 THRESHOLDS



VEKA THRESHOLD standard 62 mm



G-U THRESHOLD standard 50 mm




G-U THRESHOLD flatstep 24 mm



G-U THRESHOLD barrier-free 50 mm



G-U THRESHOLD barrier-free with drainage 50 mm



ACTIVE SASH

7150

G-U THRESHOLD comfort 50 mm